

### DESCRIPTION

A polyether polyurethane foam which meets the requirements of Schedule 1 Part 1 of The Furniture and Furnishings (Fire) (Safety) Regulations.

### TYPICAL PHYSICAL PROPERTIES

Physical properties are measured using test methods described in BS EN ISO 845:1995. (Determination of Density), BS EN ISO 2439 (Determination of Hardness) and BS EN ISO1798 (Determination of Tensile Strength and Elongation) and BS EN ISO1856 (Determination of compression).

**Piece Density Range** **29-31 kg/m<sup>3</sup>**

**Hardness (40%) Strength** **130-160N**

**Nominal Tensile Strength** **Min 50 kPa.**

**Nominal Elongation at Break** **Min 90%.**

**Nominal Compression Set** **Max 12%**

Standard colour is yellow.

Vitafoam reserve the right to update product data information without prior notice.  
Issued 05/2018

For product samples and to find out more about how you could utilise Vitafoam's unique properties, contact us:

**T: 0161 655 2744**

**E: [info@vcfuk.com](mailto:info@vcfuk.com)**

**[www.vitafoam.co.uk](http://www.vitafoam.co.uk)**



Registered Office:  
Oldham Road,  
Middleton,  
Manchester,  
M24 2DB  
Company Reg No: 621497