

### DESCRIPTION

A polyether polyurethane foam which meets the requirements of Schedule 1 Part 1 of The Furniture and Furnishings (Fire) (Safety) Regulations.

### TYPICAL PHYSICAL PROPERTIES

Physical properties are measured using test methods described in BS EN ISO 845 (Determination of Density), BS EN ISO 2439 (Determination of Hardness) and BS EN ISO1798 (Determination of Tensile Strength and Elongation).

<b>Nominal Piece Density Range</b>	<b>50-52 kg/m<sup>3</sup></b>
<b>Nominal Hardness (40%) Strength</b>	<b>90-120N</b>
<b>Nominal Tensile Strength</b>	<b>Min 80 kPa.</b>
<b>Nominal Elongation at Break</b>	<b>Min 180%.</b>
<b>Nominal Compression</b>	<b>Max 4%</b>

Standard colour is gold.

Vitafoam reserve the right to update product data information without prior notice.  
Issued 11/2014

For product samples and to find out more about how you could utilise Vitafoam's unique properties, contact us:

**T: 0161 655 2705**

**E: [info@vcfuk.com](mailto:info@vcfuk.com)**

**[www.vitafoam.co.uk](http://www.vitafoam.co.uk)**



Registered Office:  
Oldham Road,  
Middleton,  
Manchester,  
M24 2DB

Company Reg No: 621497