

DESCRIPTION

A combustion modified high resilience foam suitable for luxury contract seating. Complies with the requirements of Schedule 1, Part 1, The Furniture and Furnishings (Fire) (Safety) Amended Regulations 1989. also meets the requirements of FAR/JAR Part 25:App. F Part 1 (Vertical test)/EASA CS.25.853

TYPICAL PHYSICAL PROPERTIES

Physical properties are measured using test methods described in BS EN ISO 845:1995. (Determination of Density), BS EN ISO 2439 (Determination of Hardness) and BS EN ISO1798 (Determination of Tensile Strength and Elongation) and BS EN ISO1856 (Determination of compression).

Nominal Piece Density Range	40-44 kg/m³
Nominal Hardness (40%) Strength	220-280N
Nominal Tensile Strength	Min 130 kPa.
Nominal Elongation at Break	Min 120%.
Nominal Compression Set	Max 10%

Standard colour is blue.

Vitafoam reserve the right to update product data information without prior notice.
Issued 11/2014

For product samples and to find out more about how you could utilise Vitafoam's unique properties, contact us:

T: 0161 655 2705

E: info@vcfuk.com

www.vitafoam.co.uk



Registered Office:
Oldham Road,
Middleton,
Manchester,
M24 2DB

Company Reg No: 621497